For Residential and Commercial Applications


Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

199A Drain Waste Connector - Compression x Female Sweat

Use: For use with waste drainage systems

Design Features:

- Extruded one-piece body eliminates potential for pin holes and porosity
- Clean, uniform threads insure positive threaded connections and reduces potential for cross-threading
- Full flow waterway with smooth, uniform internal surfaces
- Uniform wall thickness with close dimensional tolerance assurance means no variations
- **Smooth finish** simplifies assembly with no burrs or rough surfaces to catch or hang up during installation



Operating Specifications:

Temperature: 40° to 140°F

MATERIAL SPECIFICATIONS				
Fitting Body	Brass			
Compression Ring	Brass			
Nut	Zinc die cast			

PART DIMENSIONS (Inches)					
Model	HEX. A	DIM. B	ост. с		
199A	2.00	1.54	2.00		

Part Listing:

199A 1-1/2" OD compression x 1-1/2" ID female sweat, rough finish

B

Fitting Body

Nut

This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company, and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.

