

Central Brass Company, Inc. 3325 S. Garfield Ave.

Commerce, CA 90040 (800) 321-8630 www.centralbrass.com

INSTALLATION

Tools:









Adjustable Wrench

Plumbers Putty

Teflon Tape

Rag

Model Number: 1109 Series

Warnings and Notes:


Check with local plumbing code requirements before installation. This product should be installed by a local listed plumber.

Do not use plumbers putty on threads.



Installation Steps:


Pop-Up Drain




(1) Remove pop-up flange from body




(5) Remove pivot rod nut from pop-up body, ensure the washers is in place, insert pivot rod, tighten pivot rod nut back to pop-up body.




(2) Place a ring of plumbers putty on the bottom of flange.



(6) Push pivot rod down, insert drain plug carefully. Test to ensure drain plug works properly.



(3) Insert pop-up flange through drain hole and attach flange to body. Use Teflon tape to thread tail piece to Pop-up drain body. Ensure the pop-up outlet faces towards the back of the sink. Tighten the locknut securely with a wrench. Do not overtighten.



(7) Connect lift rod strap to pivot rod by using clip. Tighten the thumbscrew to connect lift rod strap to pop-up lift rod.



(4) Remove the excess plumbers putty. Connect the trap (check manufacturer's instructions for installation).



For more care information or trouble shooting inquiries about your Central Brass product, please call:

Central Brass Company, Inc. (800) 321-8630

Monday-Friday 8 AM to 8 PM EST (5 AM to 5 PM PST)

www.centralbrass.com