

# LEGIOMIX®

## Electronic mixing valve, ANSI 150 Flanged



### 6000 series

Submittal Data 03603 NA — Issue Date 08/2021

#### Application


The electronic mixing valve is used in centralized systems that produce and distribute domestic hot water. It maintains the temperature of the domestic hot water delivered to the user when there are variations in the temperature and pressure of the hot and cold water at the inlet or in the draw-off flow rate. The LEGIOMIX® electronic mixing valve provides precise temperature control over very low and very high flow rate demand, minimal pressure drop with a ball valve control element, automatic self-cleaning to prevent scale formation and easy-to-use digital interface with data logging, alarming and status indication. The LEGIOMIX electronic mixing valve is furnished with a controller with LCD user interface that provides a set of programs for circuit thermal disinfection to kill Legionella. The controller is configurable via keypad, or local or remote computer. Depending on the type of system and habits of the user, temperature levels and operation times can be programmed as desired. In addition, it comes standard with monitoring and remote control connections.



#### Typical Specification

Furnish and install on the plans and described herein, a Caleffi 6000 series LEGIOMIX electronic mixing valve as manufactured by Caleffi. Each valve with controller must be designed with programmable thermal disinfection. The valve design must include a DZR low-lead brass body, chrome-plated low-lead brass ball and peroxide-cured EPDM hydraulic seals. Flanges shall be galvanized cast iron slip-on style, ANSI B16.5 150 CLASS RF. The actuator must be 3-wire floating fail-in-place with integral position indicator, 24 VAC 50/60 Hz with self-extinguishing VO cover, protection class IP 65 (NEMA 4/4X). The controller must be 24 VAC 50/60 Hz with adjustment temperature range 70 - 185°F (20 - 85°C) and disinfection temperature range 100 - 185°F (40 - 85°C). Provided with two NTC element 10,000 ohm stainless steel temperature sensors for mixed outlet water temperature and return water temperature, strap-on style, for recirculation; and 24 VAC transformer. Choice of 11 languages with set of programs for selectable automatic scheduling circuit thermal disinfection to kill Legionella, configurable via keypad, or local or remote controller; with additional functions of daily ball rotation cycle, flush valve relay output, data logging (40 day FIFO loop buffer), alarming, and status indication. Provide with Modbus-to-BACnet gateway for BAS integration, code 755052. The valve must be ICC-ES certified to ASSE 1017, CSA B15.3, NSF 372-2011, low lead laws and listed by ICC-ES; and meet codes IPC and UPC for use in accordance with the US and Canadian plumbing codes. Meets the requirement of CSA Z317.1 Special Requirement for Plumbing Installations in Health Care Facilities, certified by ICC-ES. Each valve shall be Caleffi model 6000 series or approved equal. (See product instructions for specific installation information.)

#### Dimensions



Code	A	B	C	D	E	F	G	Wt (lb)
600060A	2½" FLG	9 ¼"	23 11/16"	10 13/16"	5½"	7"	4"	30
600080A	3" FLG	9 ¼"	23 11/16"	10 13/16"	5½"	7"	4"	42

#### Recommended Flow rates (gpm/lpm)

Size	2½"	3"
Minimum (1)	17.0 / 64	22.0 / 83.3
Design Flow (2)	288 / 1,090	329 / 1,245
Maximum (3)	470 / 1,780	537 / 2,033
Cv	105	120

- (1) To ensure stable operation and a ± 3° F accurate temperature control Minimum flow rate is 0 gpm when recirculation flow rate is greater than or equal to the valve size minimum flow rating.
- (2) Suggested maximum flow rate for optimum modulating control (at 7.5 psid pressure drop).
- (3) Maximum recommended differential pressure is 20 psid to ensure stable operation and accurate temperature control.

**CONSULT TECHNICAL BROCHURE 1086 FOR COMPLETE GUIDANCE ON SIZING AND SELECTION.**

**Technical specifications**

**Valve body**

Materials: - Body: DZR low-lead brass  
 - Ball: 316 stainless steel  
 - Slip-on flanges for sizes 2½" & 3": galvanized carbon steel  
 - Hydraulic seals: peroxide-cured EPDM  
 - Ball seats: PTFE

Max. body pressure rating (static): 230 psi (16 bar)  
 Max. operating pressure: 150 psi (10 bar)  
 Max. inlet temperature: 212°F (100°C)  
 Temperature gauge scale: 30 - 210°F  
 Suitable fluids: water  
 Max. water hardness: 10 grains

Main connections: -ANSI B16.5 150 CLASS RF 2½" & 3"

**Actuator, 3-wire floating fail-in-place**

Electric supply: 24 VAC - 50/60 Hz  
 Power consumption: 6 VA  
 Protection cover: self-extinguishing VO  
 Protection class: IP 65 (NEMA 4/4X)  
 Ambient temperature range: 14 - 130°F (-10 - 55°C)  
 Electric supply cable length: 31½" (0.8 m)  
 Max. distance for control signal wire:  
 500 ft (150 m) cable 2 conductor x AWG 18  
 800 ft (250 m) cable 2 conductor x AWG 16

**Controller, LCD user interface/display**

Materials: - Housing: self-extinguishing ABS, color white RAL 1467  
 - Cover: self-extinguishing SAN, smoked transparent  
 Electric supply: 24 VAC (min 21.6, max 26.0 VAC) - 50/60 Hz  
 (50 VA Class 2 24 VAC transformer is included)  
 Power consumption: 6.5 VA  
 Adjustment temperature range: 70 - 185°F (20 - 85°C)  
 Disinfection temperature range: 100 - 185°F (40 - 85°C)  
 Ambient temperature range: 32 - 120°F (0 - 50°C)

Protection class: IP 54 (wall mounting)  
 (Class II appliance)

Mounting bracket: DIN rail

Mixing valve actuator current draw: 1 A max / 24 V  
 Alarm relay (R2): 5 A resistance (2 A inductance) / 24 V  
 Contact rating (R1, R3, R4): 10 A resistance (2 A inductance) / 24 V  
 (A 50 VA Class 2 120/24 VAC transformer is included)  
 Fuses: 1 (main): 80 mA  
 Fuses: 2 (mixing valve): 1 A  
 Charge reserve: 15 days in the event of electric supply failure,  
 with a 3 cell rechargeable 3.6 V 140 mAh buffer battery  
 Battery recharging time: 72 hours  
 Approvals: CE, FCC part 15

**Temperature sensors**


Body material: stainless steel  
 Type of sensitive element: NTC  
 Working temperature range: 14 - 260°F (-10 - 125°C)  
 Resistance: 1000 Ohms at 77° F (25° C)  
 Time constant: 2.5  
 Max. distance for mixed outlet or return (recirculation) sensor:  
 500 ft (150 m) cable 2 conductor x AWG 18  
 800 ft (250 m) cable 2 conductor x AWG 16

**Mixing valve performance**

Accuracy: ± 3° F (± 2° C)  
 Max. operating differential pressure (dynamic): 20 psi (1.4 bar)  
 Max. ratio between inlet pressures (H/C or C/H): 2.1

**Certifications**

1. ASSE 1017/CSA B125.3, certified by ICC-ES, file PMG-1357.
2. Meets the requirement of CSA Z317.1 Special Requirement for Plumbing Installations in Health Care Facilities, certified by ICC-ES, file PMG-1357.
3. Complies with NSF/ANSI 372, Drinking Water System Components Lead Content Reduction of Lead in Drinking Water Act, California Health and Safety Code 116875S.3874, Reduction of Lead in Drinking Water Act, as certified by ICC-ES, file PMG-1360.



1. LEGIOMIX digital controller
2. Mixing valve
3. Mixing valve 24V 3-wire actuator
4. Mixed outlet water temperature sensor
5. Return water (recirculation) temperature strap-on sensor
6. Mixed outlet water temperature gauge
8. Removable operating lever

**Package contents**

- Digital controller, consisting of housing and base for electric connection
- DIN bar and mounting wall anchors
- Mixing valve with temperature gauge
- 24 VAC 3-wire floating Actuator
- Mixed outlet water temperature sensor
- Return water temperature strap-on sensor
- Spare fuses
- Installation and commissioning manual
- 24 VAC transformer

We reserve the right to change our products and their relevant technical data, contained in this publication, at any time and without prior notice. Contractors should request production drawings if prefabricating the system.

Job name \_\_\_\_\_  
 Job location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Mechanical contractor \_\_\_\_\_  
 Contract P.O. No. \_\_\_\_\_  
 Representative \_\_\_\_\_

Size \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Service \_\_\_\_\_  
 Tag No. \_\_\_\_\_  
 Notes \_\_\_\_\_