

26 728

EUPHORIA®

COOLTOUCH THERMOSTATIC SHOWER SYSTEM

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE CoolTouch® no risk of scalding
- GROHE TurboStat® compact cartridge with wax thermoelement
- Exposed thermostatic temperature control with SafeStop at 100°F / 38°C
- GROHE SafeStop® Plus optional temperature limiter at 110°F (43°C) included
- 17 ¾" Horizontal swivel shower arm
- GROHE QuickFix® (upper bracket adjustable)
- Switch between hand shower and shower head via built-in diverter
- 2 Discrete functions (non-shared)
- Bar with adjustable height hand shower holder
- Includes adaptors for easy installation (depth adjustable)
- 69" Rotaflex metal shower hose (1750mm) (28 025)
- CALGreen compliant
- Shower head and hand shower are NOT included (sold separately)
- Protected against backflow
- Optional: GROHE EasyReach tray (26 362 LN1) (sold separately)
- Optional: Spacer Disc ¼" (27 180) (sold separately)
- Optional: Longer Rail 46" (1166mm) (48 053) (sold separately)
- Optional: Shorter Rail 34" (866mm) (48 054) (sold separately)
- Optional: Service Stop (12 400) (sold separately)



PRODUCT FEATURES:

- GROHE CoolTouch®
- GROHE QuickFix®
- SafeStopPlus
- GROHE StarLight®
- GROHE TurboStat®

CERTIFICATIONS:

- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

AVAILABLE FINISHES:

- 26728000** GROHE StarLight® Chrome
- 26728ENO** Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722
We reserve the right to make revisions without notice to product specifications.
For the most current Specification Sheet, go to www.grohe.us.
03-17-2021

PART OF **LIXIL**

26 728

EUPHORIA®

COOLTOUCH THERMOSTATIC SHOWER SYSTEM

Pure Freude
an Wasser



TECHNICAL DATA:

