


JASSOTHERADO

Designer Collection Specifications VL5535 AirMasseur[®] -Soaking







Patents recieved or pending

| Drop-in-Hole Size: | See Diagram |
|---------------------------|-----------------------|
| Operating Capacity: | 43 Gal. |
| Overflow Capacity: | 70 Gal. |
| Floor Loading / sq.ft. | |
| (AM/Soak): | 44.6 / 41.4 lbs. |
| Carton Weigh (AM/Soak) t: | 116 / 72 lbs. |
| Cube: | 39.7 ft. ³ |

Note: The blower extends approximately 1" past the end radius of the bath. This requires angling the bath into the drop-in hole.

Construction: Fiberglass reinforced acrylic bath with Level Form[™] full-support base.

We provide products listed with Intertek ETL SEMKO (Edison Testing Laboratories) U.S. and Canadian and with International Association of Plumbing and Mechanical Officials (IAPMO). Consult factory with your listing requirements.





JASON.

JASON

Standard

Premiei

A 120V system that includes a 1HP, variable speed blower with integral heater; automatic purge cycle; (2) Chromatherapy mood lights; Automatic Ozone System; an electronic control that operates blower and blower speed for continuous, wave, or massage pulse modes; and a 20-minute timer.

A 120V system that includes a 1HP, variable speed blower

with integral heater; automatic purge cycle; an electronic control that operates blower and blower speed for continuous, wave, or massage pulse modes; and a 20-minute timer.

A 120V system that includes a 1HP, variable speed blower with integral heater; automatic purge cycle; (2) Chromatherapy mood lights; Automatic Ozone System; a digital control with LCD display; low water level and temperature sensors; enhanced user control options; a 20-minute timer; and Bluetooth Sound Immersion System.

Control keypad operates blower and blower speed for continuous, wave, or pulse massage modes, LED Chromatherapy lights, and shows equipment status, water tempurature, and time remaining.