

SUBMITTAL SHEET

JOB NAME	ITEM TAG
JOB LOCATION	PART NUMBER
CONTRACTOR	DATE
ENGINEER APPROVAL	DATE

BALL HOSE BIBB, EXTENDED HANDLE

Model T-537L



- Manufactured in an ISO 9002 accredited facility.

Positive quarter-turn ball-type closure is more durable than low-pressure valves.

The 1/2" T-537L has a combination 1/2" mip x 1/2" solder inlet.

Forged brass construction.

Full flow design is superior to traditional stop-type valves.

Extended handle moves the operators hands away from the sharp hose bibb threads.

Working Pressure, Non-Shock (PSI)

Cold working pressure (CWP): 200 PSI

Saturated Steam (WSP): Not suitable for steam service

MATERIAL SPECIFICATION

PART	MATERIAL
1. Lever Handle	Dacromet-coated Steel
2. O-ring	Viton
3. Anti-friction Ring	*Teflon
4. Body	Forged Brass
5. Stem	Forged Brass
6. Handle Nut	Dacromet-coated Steel
7. Seat#1	*Teflon
8. Ball	Chrome Plated Brass
9. Seat#2	Neoprene
10. End Adapter	Forged Brass

*Teflon™ is a registered trademark of Dupont

DIMENSIONS

Size	1/2"	3/4"
A	3/4" GHT	3/4" GHT
B	3.44	3.84
C	1.25	1.45
D	3.05	3.05

Pictured
T-537L 1/2"
MIP x Sweat

