## **SPECIFICATION SHEET**



Finish

CP

CP

## **ELITE TWO HANDLE KITCHEN FAUCET**

|--|

Model #

K-5120\*

K-5120B\*

# K-5120 SHOWN

Features

**Builder Tract Pack** 

	Submitted For:
	Date:
-	C S S S S S S S S S S S S S S S S S S S

Model #:

Specific Features:

Project Name:

Acrylic Round Handles

- Spout Swivel 360°
- 7-9/16" Reach, 4-5/8" From Deck to Aerator •
- . Washerless Cartridge Operation
- 3-Hole 8" Installation ٠
- With 1.5 GPM Flow Rate .

Olympia products are engineered and manufactured to meet the following standards and codes:

ASME A112.18.1 ANSI A117.1 ANSI / NSF 61, SECTION 9 IAPMO LISTED CONTAINS NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT

\* Aerator limited to 1.5 GPM Flow Rate

Ø 55mm [023/16"] 5 145.8mm [5 3/4"] Air Gap 118.2mm [4 5/8"] Vertical Distance 70.3mm [2 3/4"] 60mm [2 3/8"] 23mm MAX 1/2-14 NPSM [7/8"] 46mm 29mm [1 1/8"] HOLE(2 PLACES) 192mm [1 13/16"] 203.<mark>2</mark>mm [8"] [7 9/16"] 260mn [10 1/4"]

> Nashville, TN www.olympiafaucets.com Olympia Faucets, Inc. © 2016 A Pioneer Industries Inc. Brand DMSPK-5120/REV. 09.16