

PEERLESS

Min.2 1/2" (64 mm) Clearance to Back Splash Recommended """ 5" 5 15/16" 5 3/16" (151 mm) (127 mm) (132 mm) 6" 2" (152 mm) [(50 mm) 모르 1 1/8"~1 1/2" 1 3/8" (35 mm) (29~38 mm) Hole Size Max. Deck Thickness 29 7/16" (747 mm) 3/8" compression fitting-ТП


RP27575▲ 50/50 Pop-Up



RP26533▲ Metal Pop-up







BATHROOM FAUCET

- Single Handle Deck Mount
- 1 or 3 Hole Sink Applications

STANDARD SPECIFICATIONS:

- Maximum 1.0 gpm @ 60 psi, 3.8 L/min @ 414 kPa
- Solid brass casted body
- One or three hole mount (escutcheon optional, included)
- Ceramic cartridge
- Red/Blue indicator markings
- Polymer braided flexible supply hose with 3/8" compression fitting - 29 7/16" (747mm) long
- Models with no suffix have 50/50 pop-up type fitting with plated flange and stopper
- Models with suffix "M" have metal drain with pop-up type fitting with plated flange and stopper
- Models with suffix "LPU" are less pop-up

WARRANTY:

 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to
- EPA WaterSense[®]