

Project Name

Location

Prepared By



М	_	_	_
ш	U.	C	9

Status	Active	
Watts	13.5	
Volts	120V	
Ballast Type	Туре В	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Frosted	
CCT (Kelvin)	4000	
Temperature	Cool White	
CRI	82	
Lumens	1800	
Beam Spread	220	
Dimmable	Yes Dimmable	
Hours Rated	50000	
Lamp Type	Linear	
Technology	LED	
Electrical		
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or external driver required	
Power Factor	0.9	
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)	
Physical		
MOL	48	
MOD	1	
Lens Finish	Frosted	
Lens Material	Glass	
Housing Color	White	
Additional Information		
Additional Info	All glass tubo	

. reading date.	***************************************	
Additional Information		
Additional Info	All glass tube	
Tube Guard Use	Approved for use with tube guards	
Installation Notes	Install only in non-shunted lampholders	
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass	
Compliance		
Safety Listing	cULus Classified	
Location Rating	Damp	
Energy Star	No	
DLC Approved	Yes	
DLC ID	PLCHL8NP6U2O	
CEC Status	Lawful for sale in California	
RoHS Compliant	Yes	
FCC Compliant	Yes	









NSF Approved

Yes - Approved





