

# Inset Short LED Sconce Spec Sheet

SKU: 7266.74-WL Learn more at: https://sonnemanlight.com/inset-short-led-sconce

Description: LED light is directed down and reflected out from the inset interior surface of this rectilinear form. Also available as a  $\underline{\mathsf{Tall Sconce}}$ .

Yes Integral LED

120VAC 16

1100 3000K 90


Driver 1

Outlet Box TRIAC/ELV 16

1

Type #:





## Dimensions

Height:	11"
Width:	8"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Canopy/Backplate/Base Width:	7
Canopy/Backplate/Base Depth:	0.5
Canopy/Backplate/Base Height:	10

## **Electrical Specs**

Bulb(s) Included?:
Bulb 1 Type:
Bulb Quantity:
Input Voltage:
Wattage:
Initial Lumens:
Color Temperature:
CRI:
Power Supply Type:
Power Supply Quantity:
Power Supply Location:
Dimming Type:
Bulb Max Wattage:

### Installation

Installation:

Installation Orientation:

## Shipping

Carton 1 L x W x H: Carton 1 Gross Weight: Fixture Weight:

# Shade

Shade 1 Material:

### **Available Finishes**

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

#### **General Listings**

Features: Certification: Color/Finish:

Dark Sky Friendly:

Wet Rated C-ETL-US Textured Gray (.74) N

15" X 12" X

Licensed electrician

required

. Vertical

7"

5

7 LBS

Aluminum