

SPEAKMAN® SM-3420

Sentinel Mark II® Balanced Pressure Shower System

FEATURES:

- Sentinel Mark II concealed anti-scald balanced pressure shower with integral volume control and integral stops.
- Chrome plated brass wall plate with metal index.
- Chrome plated brass lever handle.
- Independent center sleeve allows up to 1 in. of rough-in variation.
- Adjustable temperature limit stop. Brass body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- Can be installed back-to-back.
- Roughing-in template.
- S-2280 Anystream® wall mounted showerhead with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum
- Four port valve with 1/2 in. female copper sweat inlets and shower outlet (tub outlet 1/2 NPT female).
- Furnished with 1/2 in. pipe plug.

FINISH:



PC

COMPLIANCE:

- ASSE 1016 & ASME 112.18.1/CSA B125.1 standards (SM-3400 valve)

OPTIONS: Add suffix to model

- Anchor plate assembly -AP
- Ball joint -BJ
- Contractor Packs Available

WARRANTY:

- 5 year limited



NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.
 2. Unless otherwise specified all inlets and outlets are 1/2" female copper sweat. 3. For ADA mounting locations consult ADAAG, ANSI A17.1, or state regulations.

DIMENSIONS:

