ON-GRADE ADJUSTABLE FLOOR DRAIN

842 series

SPECIFICATION

Sioux Chief 842 Series adjustable floor drain shall be used where necessary in drainage systems. Floor drain shall have a Sch. 40 hub connection, which conforms to ASTM D2665 (PVC) or D2661 (ABS). Connection to drainage system shall be made with a solvent weld joint to ABS/PVC pipe. Strainer of floor drain shall fasten into female threaded brass inserts. Strainer shall be heel-proof and meet applicable load requirements for intended use. Trap primer port shall be threaded ½" FIP for knockout connection.

MATERIALS

ring/strainer: nickel-bronze, 304 stainless steel, brass top housing: ABS with threaded brass inserts adapter body: ABS or PVC

STRAINER LOAD RATING

nickel-bronze/brass: 1,000 lbs. (light duty, pedestrian traffic) stainless steel: 2,000 lbs. (light duty, pedestrian traffic)

STRAINER FREE-AREA

2" drain	12.75 in ²
3" drain (standard top)	12.75 in ²
3" drain (large top)	16.4 in ²
4" drain	16.4 in ²

DIMENSIONS

A: connection size $2" \times 3"$, $3" \times 4"$, or 4" Sch. 40 hub *

B: top diameter


2" drain 4½"
3" drain (standard top) 51/8"
3" drain (large top) 7"
4" drain 7"

C: overall height

Create Item Number


2" drain 43%" -51%" 3" drain (standard top) 43%" -51%" 3" drain (large top) 51%" -61%" 4" drain 53%" -61%"

D: trap primer port ½" FIP thread for knockout connection





842-3PNQ



842-<u>ABCD</u>

e.g. 842-3PNQ = 3" PVC drain with square nickel-bronze strainer and ring

<u>A</u>	CONNECTION	<u>C</u>	RING & STRAINER		ACCE	SSORIES
□ 2	2" Sch. 40 hub	□ BQ	square brass		863-FA	aluminum condensate
□ 3	3" Sch. 40 hub (standard top)	□ NQ	square nickel-bronze			funnel
□ 36	3" Sch. 40 hub (large top)	□ SQ	square stainless steel		863-FN	nickel condensate funnel
□ 4	4" Sch. 40 hub				863-FN0	oval nickel condensate
		D	OPTIONS (FACTORY INSTALLED)			funnel
<u>B</u>	ADAPTER	_ ∨	vandal-resistant strainer screws		842-UM	45%" stainless steel
□ A	ABS adapter	□Н	hinged strainer ¹			sediment screen 1
- D	PVC adapter		S	1	uco with 942	1 or 942.26 only

1 use with 842-4_ or 842-36_ only

^{*} Adapters fit over 2"/inside 3" pipe, or over 3"/inside 4" pipe