ADJUSTABLE CLEANOUT

851 series

SPECIFICATION

Sioux Chief 851 Series adjustable cleanout shall be used where necessary in drainage systems. Cleanout shall have a cast iron no-hub connection. Cleanout cover shall meet applicable load requirements for intended use. Cleanout shall include a slotted, polypropylene cleanout plug, with threaded brass insert to accept cover screw.

Item # Submitted
Job Name
Location
Engineer
Contractor
PO# TAG

MATERIALS

adapter body: cast iron

ring/cover: nickel-bronze, tenzalloy, or cast iron

set screws: square head, 1/4-20

cover screw: stainless steel, Phillips head, 1/4-20

cleanout plug: slotted polypropylene with threaded brass insert




nickel-bronze: 2,500 lbs. (medium duty) tenzalloy: 1,250 lbs. (light duty) cast iron: 7,500 lbs. (heavy duty)



851-23i

DIMENSIONS

	nickel/ tenz	cast iron	laminated cast iron
A: ring/cover diameter			
4" cleanout	6"	6"	71/8"
6" cleanout	83/8"	71/8"	71/8"
B: height			
4" cleanout	31/4"-41/2"	43/4"-53/4"	4"-6"
6" cleanout	33/8"-5"	4½"-6"	43/4"-61/4"
C: plug			
4" cleanout	4" MIP	4" MIP	4" MIP
6" cleanout	5" MIP	5" MIP	5" MIP



Create Item Number

851-ABC

e.g. 851-23iNV = 3" cast iron no-hub cleanout with nickel-bronze laminated cast iron cover with vandal-proof screw

<u>A</u>	CONNECTION SIZE	<u>B</u>	RING & COVER	<u>D</u>	OPTIONS (FACTORY INSTALLED)
□ 24	4" no-hub	\square N	nickel-bronze	\Box V	vandal-resistant cover screws
□ 26	6" no-hub	□ T	tenzalloy	□S	stamped cover, specify letters ¹
		□i	cast iron	\Box C	carpet marker
		□ iN	nickel-bronze laminated cast iron	1 NO	T available with cast iron ring & cover