



SYMMONS® SHOWEROFF®

the smart choice™

Shower On, SHOWEROFF!

SHOWEROFF metering shower valves and systems from Symmons provide a positive solution to the issues of water waste and hot water energy savings.

A durable, piston-actuated metering shower valve, SHOWEROFF provides a full shower flow for approximately 45 seconds,* and never forgets to shut itself off. The cycle can be repeated indefinitely, but the shower can not be left running. Ideal for public showers, detention facilities or any shower application where there is a need to positively control shower water usage. As a single supply metering valve, SHOWEROFF can be supplied with a single cold or tempered water supply line.



(*Shower cycle time can vary depending on water temperature and pressure.)

Metering Shower Valves
and Systems



4-420

SHOWEROFF concealed metering shower valve with integral stop and 1/2" sweat connections. All mounting fasteners for valve are vandal-resistant recessed hex socket type.



4-427

SHOWEROFF concealed metering shower valve with integral stop and 1/2" IPS back connections. All mounting fasteners for valve are vandal-resistant recessed hex socket type.



4-427-R

SHOWEROFF concealed metering shower valve with integral stop, 1/2" IPS back connections and escutcheon with rear mounting plate and thru bolts, rear access corridor model.



4-428

SHOWEROFF concealed metering shower valve with integral stop for thin wall and 1/2" IPS connections. All mounting fasteners for valve are vandal-resistant recessed hex socket type.



4-428-R

SHOWEROFF concealed metering shower valve with integral stop for thin wall, 1/2" IPS connections and escutcheon with rear mounting plate and thru bolts, rear access corridor model.



4-425

SHOWEROFF exposed metering shower valve with integral stop and wall flange.

Modifications (4-425 only):
Suffix A: Anchor Plate for ceramic tile
Suffix B: Back Plate & Bolts



3-310

3-310 SHOWEROFF concealed metering shower valve with integral stop and 1/2" IPS back connections (model 4-427). Fre-Flo institutional showerhead with adjustable spray (model 4-295B). All mounting fasteners for valve and head are vandal-resistant recessed hex socket type.

3-320

SHOWEROFF concealed metering shower valve with integral stop for thin wall and 1/2" IPS connections (model 4-428). Fre-Flo institutional showerhead with adjustable spray (model 4-295B). All mounting fasteners for valve and head are vandal-resistant recessed hex socket type.

3-325

SHOWEROFF concealed metering shower valve with integral stop and 1/2" sweat connections (model 4-420). Fre-Flo institutional showerhead with adjustable spray (model 4-295). All mounting fasteners for valve and head are vandal-resistant recessed hex socket type.



3-310-R

SHOWEROFF concealed metering shower valve with integral stop, 1/2" IPS back connections and escutcheon with rear mounting (model 4-427-R). Fre-Flo institutional showerhead with adjustable spray (model 4-295B). Back plate and thru bolts for extra thick wall. Mounting fastener for head is vandal-resistant recessed hex socket type.

3-320-R

SHOWEROFF concealed metering shower valve with integral stop for thin wall, 1/2" IPS connections and escutcheon with rear mounting (model 4-428-R). Fre-Flo institutional showerhead with adjustable spray (model 4-295B). Back plate and thru bolts for extra thick wall. Mounting fastener for head is vandal-resistant recessed hex socket type.



W-330

SHOWEROFF exposed metering shower valve with integral stop (model 4-425), wall flange, union and street ell with escutcheon. 20" head riser with extended head bracket (model 4-445). Fre-Flo showerhead with adjustable spray (model 4-285).