IWA 4S + DryDock™ 12 in stock

IWA-4-S-DD-12-S-BA



IWA-4-S-DD-12-S-GT



IWA-4-S-DD-12-S-WH



IWA-4-S-DD-12-S-GR



Designer White Resin*

Specifications

Single bowl Users: 1

Wash Tools included: Five (8 pcs)

Outside dimensions: 57 1/2" x 19 1/2" x 2 1/16"

Counter top cutout: 56 1/2" x 18" Minimum cabinet size: 60" or 150cm

Minimum clearance required for DryDock™

below counter top: 2"

DryDock™ location: Drain side (S)

Wash Tools included

- (1) Upper Tier Drying Rack 12 1/4" x 18"
- (1) Lower Tier Mini Drying Rack 6" x 17"
- (1) Lower Tier Utensil Caddy 6" x 17"
- (1) Lower Tier Drying Rack 12 1/4" x 17"
- (1) 12" Upper Deck

Basin construction

16GA 316L stainless steel indoor/outdoor Angel finish

Two tier design


Star™ groove pattern


Reversible side drain

Elevated drain cover included Limited Lifetime Warranty

Made in the USA

ASME A112.19.3/CSA B45.4 certified





- Suggested maximum inside corner radius of counter top cutout 3/8"
 Center Tap hole diameters 2" behind cutout
 1. Galley Tap 1.36" min hole diameter (1 1/2" min hole diameter for fast water jet cut)
 1. Galley Deck Switch 1 3/8" min hole diameter or Galley Automatic Strainer Basket knob 1" min and 1 3/8" max hole diameter
 2. Galley Hot And Cold Water Dispenser 1" 3/8" min hole diameter (1 1/2" min hole diameter for fast water jet cut) or Galley Soap Dispenser
 3. Galley Soap Dispenser
 4. Galley Soap Dispenser
 4. Galley Soap Dispenser
 4. Galley Soap Dispenser
 4. Galley Hot and Cold Water dispenser requires a minimum 8" clearance to center if installed to the right of the Galley Tap

